



# Connecting Strength

## Imagen

## Producto

## Torque



K2 Cross Clamp  
PNs: 4000135 & 4000145

12 ft-lb (16.3 Nm)



T-Bolts  
PNs:4000048 & 4000122

T-Bolts M10: 25.8 ft-lb (35.0 Nm)



Climber Set  
PNs: 4006042-H & 4006043

M8 Bolt: 10.3 ft-lb (14.0 Nm)



K2 Ground Lug  
PN:4000006-H

M8 Bolt: 10.3 ft-lb (14.0 Nm)  
Terminal Bolt: 3-5 ft-lb (3.9-6.8 Nm)



Yeti Clamp 2.0  
PN: 4000050-B

12 ft-lb (16.3 Nm)



Standing Seam Rail-less  
PN: 4000532

24 Steel 12.5 ft-lb (16.9 Nm)  
13.3 ft-lb (18.0 Nm)  
22 Steel 15 ft-lb (20.3 Nm)  
16.6 ft-lb (22.6 Nm)



Standing Seam PowerClamps  
PNs: 4000016 & 4000017

M8 Hex Bolt: 12 ft-lb (16.3 Nm)  
24 Steel 12.5 ft-lb (16.9 Nm) 13.3 ft-lb (18.0 Nm)  
22 Steel 15 ft-lb (20.3 Nm) 16.6 ft-lb (22.6 Nm)



CR Micro Inverter & OPT Mounting Kit  
PN: 4000629-H

M8 Hex Bolt: 10.3 ft-lb (14.0 Nm)



MLPE Module Frame Mounting Kit  
PN: 4000083

10.3-18.5 ft-lb (14-25 Nm)



ILSCO Lug  
PN: 4000960

Mounting Bolt:  
6.2 ft-lb = 8.40 Nm  
Terminal Bolt:  
3-5 ft-lb (3.9-6.8 Nm)

